

FOUR
STROKE

MFS2.5B



Exceed the European
Union emission standards.



California C.A.R.B.
three star rating
for ultra-low emissions.

FOUR
STROKE

Specifications

Type		Four Stroke
Maximum output	KW (PS)	1.8 (2.5)
Maximum operating range	r/min	4500-5500
Fuel consumption at W.O.T	L/Hr (gal/Hr)	1.0 (0.26)
Number of cylinder		1
Bore x Stroke	mm (in)	55x36 (2.17x1.42)
Displacement	ml (Cu in)	86 (5.25)
Engine lubrication system		Splash
Starting system		Manual
Spark plug		NGK DCPR6E
Ignition timing	degree	BTDC3°- BTDC25°
Alternator output		-
Engine oil		4-Stroke Engine Oil
Engine oil capacity	L (qt)	0.3 (0.32)
Fuel tank capacity	L (gal)	1 (0.26)
Speed control		Twist grip type
Gear reduction ratio		2.15 (13:28)
Emission Compliance		EU & EPA & CARB 3-Star

FOUR STROKE

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	S/L
Electric Starter	-
Manual Recoil Starter	●
Decompression Release	-
Engine Stop Switch Lanyard	●
Alternator	-
Transom	15/20
Propeller	●
Analog Tachometer	-
Analog Trim Meter	-
Remote Control Box	-
12L (3.1 Gal) Plastic Fuel Tank	-
1L (0.26 Gal) In-tank	●
Tool Kit	●
Emergency Starter Rope	●
Spare Spark Plug	●
Owners Manual	●

● Standard ○ Optional



1-Cylinder



Thermostat



Built-in Tank



Throttle Friction



Forward - Neutral



360° Full Pivot Steering



Steering Friction Adjustment
(FOR TILLER HANDLE MODEL)



High Solid Paint Coating



Light Weight

FOUR STROKE

KLIMASKLEP, ul. Orzechowa 3, 72-010 Przęsocin (koło Szczecina)
tel.: (91) 432-43-42, tel.: (91) 432-43-49
e-mail: kontakt@klimasklep.pl, www: www.KlimaSklep.pl