

FOUR
STROKE

MFS6C



Exceed the European
Union emission standards.

FOUR
STROKE

Specifications

Type		Four Stroke
Maximum output	KW (PS)	4.4 (6)
Maximum operating range	r/min	5000-6000
Fuel consumption at W.O.T	L/Hr (gal/Hr)	2.0 (0.53)
Number of cylinder		1
Bore x Stroke	mm (in)	59x45 (2.32x1.77)
Displacement	ml (Cu in)	123 (7.50)
Engine lubrication system		Trochoid pump
Starting system		Manual
Spark plug		NGK DCPR6E
Ignition timing	degree	BTDC0°- BTDC25°
Alternator output		12V 60W 5A
Engine oil		4-Stroke Engine Oil
Engine oil capacity	L (qt)	0.45 (0.47)
Fuel tank capacity	L (gal)	12 (3.17)
Speed control		Twist grip type
Gear reduction ratio		2.15 (13:28)
Emission Compliance		EU & EPA & CARB 3-Star

FOUR STROKE

Specifications and descriptions are subject to change without notice.

Standard & Optional Equipments

Type	L/UL
Electric Starter	-
Manual Recoil Starter	●
Decompression Release	●
Engine Stop Switch Lanyard	●
Alternator	●
Rectifier	●
Power Tilt	-
Transom	20/25
Propeller(High Thrust)	●
Analog Tachometer	-
Analog Trim Meter	-
Remote Control Box	-
12L (3.1 Gal) Plastic Fuel Tank	●
Tool Kit	●
Emergency Starter Rope	●
Spare Spark Plug	●
Owners Manual	●

● Standard ○ Optional



1-Cylinder



Alternator



Charging System



Thermostat



Throttle Friction



Steering Friction Adjustment
(FOR TILLER HANDLE MODEL)



High Thrust Propeller



High Solid Paint Coating



Light Weight



Sail Boat Model



Front Shift Control

FOUR STROKE